

NEXT SOFTWARE – DATA STRUCTURES



Motivation

HM Shortcomings

- Complicated data structures
 - Z-index
 - Ambiguous data model (TComDataCU)
- Bad code readability
 - Complicated memory operations are intermixed with general data flow
 - Lack of data and logic encapsulation
- Complicated extensibility
 - Data structures were designed with strict assumptions (e.g. square blocks)
 - How many ideas were discarded because of erroneous implementation?

Goals

NextSoftware design principles

- Simple unambiguous data model
 - Modern OO-design, yet fast and sleek
- Global pixel addressing
 - Elimination of Z-index usage
 - Elimination of 2-level (CTU→Z-Index) signal addressing
- Encapsulation of trivial operations (e.g. memory operations)
 - Allows for better readability of general flow
- Better code readability
 - Allowing for easier extensibility

HM – Model

- TComDataCU
 - Stores coding information
 - Might represent a CU or CTU (containing multiple CU's)
 - Basically a map of image position to coding information
- TComTU
 - An object allowing for easier TU structure navigation
 - Contains no actual data, but rather wraps around *TComDataCU*
- TComPicYuv
 - Stores the video signals

NextSoftware – Model Navigation

- Size, Position, Area (Position + Size)
 - Represent basic 2D navigation information
- CompArea
 - Area in a given component (block)
- UnitArea
 - Represents an area in a multi-channel signal
 - A set of blocks describing a composition of co-located components

NextSoftware – Model

Signal Storage

- AreaBuf
 - Describes the memory layout of a 2D signal in linear memory
 - Contains simple operations (copy, fill etc.)
- UnitAreaBuf
 - Describes the memory layout a multi-component 2D signal in linear memory
 - Contains simple operations (copy, fill etc.)
- PelStorage
 - A *UnitAreaBuf* which also allocates its own memory


NextSoftware – Model

Coding Information

- Picture
 - Contains input and output signals as well as metadata (slice info etc.)
- CodingUnit, PredictionUnit, TransformUnit
 - Single object for a single unit
 - Contain the corresponding information
 - Include the location information (derived from *UnitArea*)
- CodingStructure
 - Manages the *CodingUnit* and co., links them with the picture
 - Contains additional functionalities for top-down RD-search

NextSoftware – Model

UML-Diagram of the Basic Model



HM – NextSoftware Model Equivalencies

HM	NextSoftware
Z-index, (CTU)-RS-address, Depth	Position, Size, (Comp)Area, UnitArea
TComDataCU	CodingUnit, PredictionUnit, TransformUnit Operations in CU, PU, TU namespaces CodingStructure
TComTU	Partitioning is governed by Partitioner
TComPicYuv	Picture
TComPic	Picture
TComYuv	UnitAreaBuf

NextSoftware – Detailed Description

CodingStructure Basics

- Contains *CodingUnit* etc. objects and maps them to the picture
- A TComDataCU replacement, but globally allocated
 - Top-level *CodingStructure* contains all CU's, PU's and TU's in the frame
 - Sub-level *CodingStructure* contains a representation of a specific *UnitArea*
- After creation it's empty and needs to be filled
 - addCU/PU/TU methods create and map the specific object
 - getCU/PU/TU fetches the specific objects addressed using global *Position*
- Dynamically allocates the required resources
 - Uses *dynamic_cache* for increased performance


NextSoftware – Detailed Description

RD-Search with CodingStructure

- Designed for Top-Down approach
- Allows for local test encoding with “transparent” global context
 - Follows the well known best-temp scheme with up-propagation
- Hierarchically cascaded
 - A *CodingStructure* is set up to represent a local *UnitArea*
 - Calls outside of this *UnitArea* are forwarded to the parent *CodingStructure*
- Parent nodes are not aware of the children nodes
 - Best candidates need to be propagated to the parents


NextSoftware – Detailed Description

Hierarchical Cascading with CodingStructure




NextSoftware – Detailed Description

Hierarchical Cascading with CodingStructure



NextSoftware – Detailed Description

Hierarchical Cascading with CodingStructure



- cs2.getCU({32, 32})
 - returns *cu2*
- cs2.getCU({16, 32})
 - returns *cu1*
- cs1.getCU({32, 32})
 - returns *nullptr*

NextSoftware – Detailed Description

Partitioner

- A simple class governing splitting (CU and TU, quad-tree and possibly others)
- Modelled as a stack – new splits are created as levels on the currently processed area
- For HEVC
 - Contains accessors for current split info (`partitioner.curr*`)
 - Depth (CU, TU) as well as the actual current *UnitArea*
- For QTBT and further (additionally to HEVC-features)
 - Allows to set split restrictions (e.g. constraint splits at a certain level)
 - Allows to perform split plausibility checks (`canSplit`)

NextSoftware – Detailed Description

Data Ownership

- Each piece of data is owned by some object, which needs to allocate and release it
- *Picture*
 - Owned by *EncLib* or *DecLib*
 - Owns signal buffers, *Slice* objects, *SEI* messages and *TileMap*
- *AreaBuf*, *UnitBuf*
 - Do not own any data
- *PelStorage*
 - Might own the buffers (depends if *create* or *createFromBuf* used for creation)
 - Owned data is stored in *m_origin* member

NextSoftware – Detailed Description

Data Ownership

- *CodingStructure*
 - Top-Layer: owned by *Picture*
 - Links to signal buffers of *Picture*, does not own them
 - Other (temporary in RD-Search): owned by *EncCu* or *IntraSearch*
 - Contains own signal buffers, owns them
 - Always owns buffers describing the structure and layout (not signal)
 - Owns transformation coefficient buffers
 - Does not own *CodingUnit* etc., only links to them through *dynamic_cache*

NextSoftware – Detailed Description

Data Ownership

- *CodingUnit, PredictionUnit, TransformUnit*
 - Owned by *dynamic_cache* – objects need to be acquired by *get* and freed by *cache*
- *TransformUnit*
 - Does not own transformation coefficient buffers
 - Links to buffers from *CodingStructure*
- *dynamic_cache*
 - Top-Level cache is global (dynamically allocated on runtime and freed on exit)
 - RD-search cache is owned by *EncCu* and *IntraSearch*

NextSoftware – Code Snippets

Iterate over all TUs in a CU (inter decompression example)

- Iterating over PUs works similar with *traversePUs(...)* call
- *firstTU* and *firstPU* can be used as fast accessors if the CU only has one TU/PU

```
// call xDecodeInterTU for all TUs in the CU described by cu
for( auto& currTU : CU::traverseTUs( cu ) )
{
    xDecodeInterTU( currTU, complID );
}
```

NextSoftware – Code Snippets

Iterate over all CUs in a specific area (CTU decompression example)

```
// iterate over all CUs which are contained in the area described by ctuArea
for( auto &currCU : cs.traverseCUs( ctuArea ) )
{
    // decompress CU
    xDecompress( currCU );
}
```

NextSoftare – Common Problems

Where is the motion information stored?

- Initially with HEVC, minimal resolution for Motion Vector storing was the PU
- New prosed tools for h.266 standard break this convention (e.g. VCEG-AZ10)
 - Sub-PU resolution for motion vector information is needed
 - Storing sub-PUs as PUs would break the logical purpose of a PU
 - Solution: additional buffer for sub-PU resolved motion information
 - Example:

```
Mv mvL0 = cs.getPU( pos )->mv[0];           // obsolete low-res call  
Mv mvL0 = cs.getMotionInfo( pos ).mv[0]; // new next-style high-res call
```

- Old call still allowed, might provide sub-resolution results
- *PU::spanMotionInfo* sets up the buffer

Fraunhofer Institute for Telecommunications, Heinrich Hertz Institute, HHI

**WE PUT SCIENCE
INTO ACTION.**

Contact:

Adam Wieckowski
adam.wieckowski@hhi.fraunhofer.de
-833

Einsteinufer 37
10587 Berlin



NextSoftware – Reference

Size, Position, Area

- Size
 - width, height : UInt – describe the size of a rectangle
- Position
 - x, y: Int – describe the 2D position of a point
- Area : Size, Position
 - a rectangle of a specific *Size* located at a specific *Position*
- CompArea : Area
 - an *Area* within a specific component (*compID*) of a multi-component signal

NextSoftware – Reference

UnitArea, CodingUnit, PredictionUnit, TransformUnit

- UnitArea
 - blocks [0..N-1]: *CompArea*
 - a multi-component compound consisting of N blocks
- CodingUnit : UnitArea
 - Describes how the area described by this *UnitArea* is coded
- PredictionUnit : UnitArea
 - Describes how the prediction signal for this *UnitArea* is to be generated
- TransformUnit : UnitArea
 - Describes how the transformation coding for this *UnitArea* is to be applied

NextSoftware – Reference

AreaBuf

- `AreaBuf<T>` (defined for `Pel` and `TCoeff` as `PelAreaBuf` and `CoeffAreaBuf`)
 - `at(x, y)` – returns the value of the signal at position (x,y)
 - `bufAt(x, y)` – returns the raw pointer to the buffer at position (x,y)
 - `subBuf(x, y, w, h)` – returns a `AreaBuf` describing an area offset by (x,y) of size (w,h)
 - `fill(val)` – fills the specified area with the defined value
 - `copyFrom(other)` – copies the contents from the other area
 - `subtract, addAvg, reconstruct, removeHighFreq` – methods replacing the functionalities of `TComYuv`
- `UnitBuf<T>` (similar interface to `AreaBuf`)
 - `bufs [0..N-1]: AreaBuf` – contains the signal descriptions for different components

NextSoftware – Reference

CodingStructure Basics

- CodingStructure
 - area: UnitArea – describes which area in the picture the *CodingStructure* spans
 - addCU(UnitArea) – creates and locates a *CodingUnit* spanning the *UnitArea*
 - getCU(Position) – returns the *CodingUnit* located at the specified *Position*
(analogue interfaces exist for *TransformUnit* and *PredictionUnit*)
 - setDecomp(CompArea) – sets the specified *CompArea* as reconstructed
 - setDecomp(UnitArea) – analogue multi-channel operation
 - isDecomp(Position) – tells if the reco. signal for the *Position* has been generated

NextSoftware – Reference

RD-Search with CodingStructure

- CodingStructure
 - initStructData(...) – clears all currently contained data (signals and coding info)
 - initSubStructure(...) – links a new *CodingStructure* at the bottom of the hierarchy
 - useSubStructure(...) – copies the coding data from a sub-structure
 - copyStructure(...) – copies to coding data from another structure, does not rely on a parent-child binding